



DESIGN

- 1) Conductor: soft copper wire AWG23 (Ø 0,565 mm)
- 2) Insulation: skin-foam-skin HDPE, Ø 1,35 mm
- 3) Pair: two conductors twisted together
Color identification of pairs:
pair 1: white / blue
pair 2: white / orange
pair 3: white / green
pair 4: white / brown
- 4) Pair shielding: Individual Al/Pet foil (metal outside)
- 5) Drain wire: tinned copper wire Ø 0,4 mm
- 6) Core wrapping with PET-film
- 7) Jacket: LSZH, thickness 0,5 mm, nominal cable Ø 6,7 mm


APPLICATION

- PBX, V.11, X.21, ISDN, Ethernet (10Base-T), ATM-25/52/155 Mbit/s, 100VG-AnyLAN, Token Ring 16/100 Mbit/s
- Fast Ethernet (100BASE-TX), Gigabit Ethernet (1000BASE-T), 2,5 Gbit/s Ethernet (2.5GBASE-T), 5 Gbit/s (5GBASE-T), 10GBASE-T, HDBaseT
- PoE, PoE+, PoE++

INSTALLATION AND OPERATION CONDITIONS

For stationary installation inside buildings, stations, structures and equipment in conditions of heightened electromagnetic impacts.
Operated on frequencies up to 500 MHz

COMPLIANCE WITH THE REQUIREMENTS

Cabling: ISO/IEC 11801-1, EN 50173-1
Cable: IEC 61156-5, EN 50288-10-1
Fire safety:
- Flame propagation – IEC 60332-1-2
- Zero halogen, no corrosive gases – IEC 60754-2
- Smoke density – IEC 61034-2
CPR class: Dca

MECHANICAL CHARACTERISTICS

Temperature range:

- During installation -10 °C ... +60 °C
- After installation -20 °C ... +60 °C

 Bending radius:

- During installation ≥ 8 cable diameters
- After installation ≥ 4 cable diameters

 Tensile stress: ≤ 85 N

ELECTRICAL CHARACTERISTICS AT 20 °C, 85 M

Parameter	Unit	Value
Capacitance	pF/m	≤ 56
Direct current resistance	Ohm/km	≤ 74
Insulation resistance	GOhm*km	≥ 5
Resistance unbalance	%	2
Signal propagation velocity	s	0,79
Propagation delay	ns/100 m	≤ 534+36/vf
Characteristic impedance in the frequency range of: 1-100 MHz 100-250 MHz 250-500 MHz	Ohm	100±15 100±22 100±25
Test voltage between cores, (DC, 2 s)	kV	2,5

TRANSMISSION CHARACTERISTICS AT 20 °C, 85 M

Frequency, MHz	1	4	10	16	20	31,25	62,5	100	125	200	250	300	400	500
Attenuation, dB, max	2,1	3,8	5,9	7,5	8,4	10,5	15	19,1	21,5	27,6	31	34	40	45
NEXT, dB, min	75	66	60	57	56	53	48	45	44	41	39	38	36	35
PS NEXT, dB, min	72	63	57	54	53	50	45	42	41	38	36	35	33	32
ELFEXT, dB, min	68	56	48	44	42	38	32	28	26	22	20	18	16	14
PS ELFEXT, dB, min	65	53	45	41	39	35	29	25	23	19	17	15	13	11
RL, dB, min	20	23	25	25	25	23,6	21,5	20,1	19,4	18	17	17	17	17

IEC 61156-5, values lower than 4 MHz are given for information only

ORDER INFORMATION

P/N	Cable name	Standard packing	Weight, kg/km
7935109	KPpVng-HF-VPE (500) 4*2*0,56 (U/FTP-cat.6A LSFROH)	Cardboard reel-in-box 305 m	48,0